

OROBICA PLAST-GOM Srl

Via Pietro Mascagni, 5 - 24060 CREDARO (BG) Italia

Tel.+39.035.4260911 - Fax +39.035.4260938

www.oroicaplastgom.it - info@oroicaplastgom.it

DN		Article Code	Dimensions				
Inch	mm	Orobica P.G.	M2 ±0,25	E +0/-0,5	C4 +0,5/-0	U1 ±0,1	W +0,1/-0
1"	25,4	056.5500	32,5	29,2	23,2	7,0	3,0
1" 1/4	31,8	056.5510	39,0	35,8	29,5	7,0	3,0
1" 1/2	38,1	056.5520	46,0	42,7	39,5	7,0	3,0
2"	50,8	056.5530	59,5	56,2	48,6	7,0	3,0
2" 1/2	62,5	056.5540	73,2	69,9	61,3	7,0	3,0
3"	76,2	056.5550	86,5	82,6	74,0	7,0	3,0
3" 1/2	88,9	056.5560	99,5	95,3	86,0	7,0	3,0
4"	101,6	056.5570	119,0	111,0	98,6	9,6	5,0

The technical drawing illustrates the cross-section of a gasket. It features a central cylindrical body with a diameter of $\varnothing C4$ and an outer diameter of $\varnothing E$. The gasket is mounted on a flange with a diameter of $\varnothing M2$. The flange has a thickness of 4 units. The gasket itself has a thickness of 2.5 units. The total thickness of the assembly is 5 units. The width of the flange is denoted by W.