

DIN 11864-1-2-3:2008-11				BRITISH STANDARDS		Article Code Orobica P.G.	d15		S	
"A"	"B"	"C"					mm	Inch	mm	Inch
DN	DN/OD	DN/OD		DN						
		Inch	mm	Inch	mm					
10	13.5	1/2"	12,70			056.3200	12,00 ±0,19		3,50 ±0,10	
	17.2						16,00 ±0,20		3,50 ±0,10	
15		3/4"	19,05			056.3201	18,00 ±0,21		3,50 ±0,10	
	21,3						20,00 ±0,22		3,50 ±0,10	
20						056.3202	22,00 ±0,24		3,50 ±0,10	
		1"	25,40			056.32021	24,00 ±0,25		3,50 ±0,10	
	26,9						26,00 ±0,26		3,50 ±0,10	
				1"	25,40	056.3010	27,10 ±0,25	1,070 ±0,010	6,30 ±0,15	0,248 ±0,006
25						056.3203	28,00 ±0,28		3,50 ±0,10	
	33,7						32,00 ±0,32		5,00 ±0,13	
32						056.3204	34,00 ±0,33		5,00 ±0,13	
		1" 1/2	38,10			056.32041	37,00 ±0,36		5,00 ±0,13	
				1" 1/2	38,10	056.3020	39,70 ±0,37	1,562 ±0,015	6,30 ±0,15	0,248 ±0,006
40						056.3205	40,00 ±0,38		5,00 ±0,13	
	42,4						40,50 ±0,39		5,00 ±0,13	
	48,3						46,50 ±0,44		5,00 ±0,13	
		2"	50,80			056.32051	50,00 ±0,46		5,00 ±0,13	
50						056.3206	52,00 ±0,48		5,00 ±0,13	
				2"	50,80	056.3030	52,40 ±0,48	2,062 ±0,019	6,30 ±0,15	0,248 ±0,006
	60,3						58,50 ±0,54		5,00 ±0,13	
		2" 1/2	63,50			056.32061	62,00 ±0,56		5,00 ±0,13	
				2" 1/2	63,50	056.3040	65,10 ±0,56	2,562 ±0,022	6,30 ±0,15	0,248 ±0,006
65						056.3207	68,00 ±0,61		5,00 ±0,13	
	76,1						73,50 ±0,66		5,00 ±0,13	
		3"	76,20			056.32071	75,00 ±0,66		5,00 ±0,13	
				3"	76,20	056.3050	77,90 ±0,66	3,066 ±0,026	6,30 ±0,15	0,248 ±0,006
80						056.3208	83,00 ±0,73		5,00 ±0,13	
	88,9						86,50 ±0,75		5,00 ±0,13	
				3" 1/2	88,90	056.3060	92,10 ±0,75	3,625 ±0,029	6,30 ±0,15	0,248 ±0,006
		4"	101,60			056.32081	100,00 ±0,84		5,00 ±0,13	
100						056.3209	102,00 ±0,87		5,00 ±0,13	
				4"	101,60	056.3070	103,10 ±0,84	4,062 ±0,033	6,30 ±0,15	0,248 ±0,006
				4" 1/2	114,30	056.3080	116,00 ±0,88	4,562 ±0,035	6,30 ±0,15	0,248 ±0,006
125						056.3210	127,00 ±1,00		5,00 ±0,13	
150						056.3211	152,00 ±1,20		5,00 ±0,13	

